






HARDWARE DESCRIPTION	QTY.
Kit# HWKT-00032X	
M8 – 1.25 HX FLANGED NUT	18
3/8" x ¾" carriage bolts	12
3/8" Flanged nuts	12

DO NOT USE IMPACT TOOLS


PARTS INCLUDED	QTY
Step Rail	2
Rocker Panel mounting Brackets	6
RECOMMENDED TOOLS	
RATCHET	
13mm deep socket	
9/16 socket	

<u>Step 1:</u> Starting with the driver side, remove any steps and old hardware from the vehicle.





<u>Step 3:</u> Install three rocker panel brackets to the attachments points located on the backside of the channel using the supplied $3/8'' \times 3/4''$ carriage bolts and 3/8'' flanged nuts. Leave finger tight for now.





PART NUMBER: **EXD19CC-TX** PRODUCT: **EPYX HOOP STEP** APPLICATION: **2019- C RAM 1500**

<u>Step 4:</u> On the inside rocker panel there will be three-attachment point consisting of three 8mm studs coming out from the panel. These studs may be covered in paint and will need to be cleaned before the installation.



<u>Step 5:</u> An additional person is recommended for this step. Carefully install the step assembly to the three factory attachment points using the provided M8 flanged hex nuts. Leave finger tight for now.



<u>Step 6:</u> Next, adjust the step assembly up/down and front/back to level out the step rail with body panel and then tighten step to brackets at 30 ft. /lbs.



<u>Step 7</u>: Adjust the step rail to where you have approximately ¹/₄" gap between the body of the vehicle and the top of the rail.



<u>Step 8</u>: After finial adjustment, tighten all rocker panel brackets to 30 ft./lbs.

<u>Step 9:</u> Re-peat steps 3-8 for passenger side.